(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 2 October 2003 (02.10.2003)

PCT

(10) International Publication Number WO 03/081274 A1

(51) International Patent Classification⁷: GOSG 1/0967

G01S 7/02,

(21) International Application Number: PCT/NL03/00225

(22) International Filing Date: 25 March 2003 (25.03.2003)

(25) Filing Language:

Dutch

(26) Publication Language:

English

(30) Priority Data: 1020265

27 March 2002 (27.03.2002) N


- (71) Applicant (for all designated States except US): DE WILDE, Bouwe, Guustaaf, Dirk [NL/NL]; P.O.Box 132, NL-2160 AC Lisse (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): DE WILDE, Jim, Sven, Anthony [NL/NL]; P.O.Box 132, NL-2160 AC Lisse

(NL). DE WILDE, Tom, Marnix, Alexander [NL/NL]; P.O.Box 132, NL-2160 AC Lisse (NL).

- (74) Agent: VERNOUT, Robert; Sweelinckplein 1, NL-2517 GK The Hague (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE (utility model), DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: DEVICE AND METHOD FOR PREVENTING SPEEDING



(57) Abstract: A device for preventing a vehicle from speeding, which device comprises a switching device, a speedometer present in the vehicle, which is connected to said switching device and which measures the speed of the vehicle, as well as a transmitter connected thereto, wherein the switching device is so arranged that the transmitter will only transmit a signal mainly if and as long as the speed measured by the speedometer is higher than a predetermined limiting value.

WO 03/081274 A1



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.





DT09 Rec'd 1/PTO 2/7 SEP 2004

PCT/NL03/00225

10/509169

DEVICE AND METHOD FOR PREVENTING SPEEDING

The invention relates to a device for preventing a vehicle from speeding.

Speeding checks are currently being carried out to an increasing extent, at least in the Netherlands, and as a consequence an increasing number of increasingly heavy fines are being imposed. Consequently there is a need among car owners and drivers for a device by means of which the risk of receiving such fines can be reduced in an efficient and simple manner.

15

20

30

10

To that end, the device comprises a switching device, a speedometer present in the vehicle, which is connected to said switching device and which measures the speed of the vehicle, as well as a transmitter connected thereto, in which the switching device is arranged in such a manner that the transmitter will only transmit a signal mainly if and as long as the speed measured by the speedometer is higher than a predetermined limiting value. It will be understood that said limiting value preferably corresponds to the local maximum speed. The signal may be a warning signal, for example, which 25 can induce the driver to reduce the speed of the vehicle.

In a first embodiment, the device comprises inputting means, by means of which a user can adjust the limiting value at his own discretion. In a second preferred embodiment, the device comprises a GPS (Global Positioning System) position finding device, in which the limiting value is adjusted in dependence on the geographic position of the vehicle as found. This

2

latter variant is in particular advantageous if the device is connected to a database in which the geographic positions are linked to the maximum speed that locally obtains, so that the adjusted limiting value will automatically correspond to the local maximum speed at practically any moment.

In another preferred embodiment, the speedometer also comprises a GPS position finding device, in which the speed is determined in that the distance between two positions as found is divided by the time required for covering said distance.

Preferably, the transmitted signal comprises an acoustic signal for warning the driver. Furthermore, the transmitted signal preferably comprises light and/or laser pulses. Light pulses, too, constitute an efficient way of warning the driver of a vehicle, whilst laser pulses may be used effectively for causing interference with any external speed measuring equipment operating on the basis of laser techniques, assuming, of course, that this is legally allowed.

In a special preferred embodiment of the invention, the device furthermore comprises a detector for detecting external measuring equipment for measuring the speed of a vehicle, in which the switching device is furthermore so arranged that the signal will only be transmitted upon detection of said external measuring equipment. This enables the driver to adjust the speed of the vehicle in time upon detection of such measuring equipment, whilst the driver will not be unnecessarily alerted to the presence of such equipment when driving at a speed below the allowed speed.

3

The use of the aforesaid laser pulses thus makes it possible to prevent unnecessary transmission of the interference signal when the vehicle is not driving faster than the maximally allowed speed.

5

The invention also relates to a method for preventing speeding by a vehicle, in which a switching device is connected to a speedometer present in the vehicle, which measures the speed of the vehicle, in which the switching device only allows a transmitter connected thereto to transmit a signal mainly if and as long as the speed measured by the speedometer exceeds a predetermined limiting value.

The invention will now be explained in more detail by means of an embodiment which is schematically shown in Figure 1.

The Figure schematically shows a car 1 in top plan view while said car is driving on a road. The car 1 is fitted with a central processing unit 2, which is connected to a memory 20 module 3, a speedometer 4 and a loudspeaker 5. Furthermore, the central processing unit is connected to an input/output unit 6, which is fitted with a small keypad and a small display screen. In a simple embodiment, the driver inputs a limiting value as regards the speed, which may be a local 25 maximum speed, before or during a trip by means of said input/output unit 6, upon exceeding of which speed the driver wishes to hear an acoustic warning signal that will enable him to reduce his speed. The limiting value is stored in the memory module 3. The central processing unit 2 receives 30 information as to the actual speed of the car from the speedometer 4, and the central processing unit 2 activates the loudspeaker 5, which transmits a warning signal if and as

4

long as the actual speed is higher than the adjusted limiting value.

In a more extensive embodiment, the central processing unit 2 5 is also connected to a GPS receiver 7, which is capable of establishing the geographic position of the car. GPS receivers are known per se, and their operation is considered to be known, therefore. In this embodiment, the memory module 3 comprises a database in which geographic positions, in particular of the road system and the locally obtaining 10 maximum speeds, are stored. Preferably, said database is updated with new information and alterations on a regular basis. The central processing unit 2 determines the local maximum speed on the basis of the geographic position supplied by the GPS receiver and the information obtained from the database and inputs said value as a limiting value. When this is done at short intervals, the limiting value will correspond to the local maximum speed practically at alltimes.

20

25

In yet another embodiment, the central processing unit 2 is furthermore connected to a laser detector/transmitter 8, which is capable of detecting the laser signal from an external laser speed measuring device 9. If such a device is detected, and if moreover the speed of the car 1 is higher than the adjusted limiting value, the central processing unit 2 will activate the loudspeaker to transmit a special warning signal. The warning signal may also be a (flashing) light signal. In those cases where this is legally allowed, the driver may also opt to have the central processing unit 2 cause the laser detector/transmitter 8 to transmit interference light or laser pulses instead of or

5

simultaneously with the warning signal, as a result of which the measuring device 9 will be unable to carry out a speed measurement. An example of such a method for causing interference by means of laser pulses is described in International patent application WO 97/21110, and consequently it will not be discussed anew herein.

CLAIMS

25

- A device for preventing a vehicle (1) from speeding, which device comprises a switching device (2), a
 speedometer (4; 7) present in the vehicle, which is connected to said switching device and which measures the speed of the vehicle (1), as well as a transmitter (5; 8) connected thereto, wherein the switching device is so arranged that the transmitter (5; 8) will only transmit a signal mainly if and as long as the speed measured by the speedometer (4; 7) is higher than a predetermined limiting value.
- A device according to claim 1, wherein the device
 comprises inputting means (6), by means of which a user
 can adjust the limiting value at his own discretion.
- A device according to claim 1 or 2, wherein the device comprises a GPS position finding device (7) and wherein the limiting value is adjusted in dependence on the geographic position of the vehicle (1) as found.
 - 4. A device according to claim 1, 2 or 3, wherein the speedometer (7) also comprises a GPS position finding device, and wherein the speed is determined in that the distance between two positions as found is divided by the time required for covering said distance.
- A device according to any one of the preceding claims,
 wherein the transmitted signal comprises an acoustic signal.

7

- 6. A device according to any one of the preceding claims, wherein the transmitted signal comprises light and/or laser pulses.
- 5 7. A device according to any one of the preceding claims, wherein the device furthermore comprises a detector (8) for detecting external measuring equipment (9) for measuring the speed of a vehicle, wherein the switching device (2) is furthermore so arranged that the signal will only be transmitted upon detection of said external measuring equipment (9).
- 8. A method for preventing a vehicle (1) from speeding, wherein a switching device is connected to a speedometer (4; 7) present in the vehicle, which measures the speed of the vehicle (1), wherein the switching device only allows a transmitter (5; 8) connected thereto to transmit a signal mainly if and as long as the speed measured by the speedometer (4; 7) exceeds a predetermined limiting value.






FIG. I

INTERNATIONAL SEARCH REPORT

PCT/NI 03/00225

		Ī	ICIVAL 03	/ 00225
A. CLASS IPC 7	G01S7/02 G08G1/0967			
According i	- to international Patent Classification (IPC) or to both national classifi	cation and IPC		
8. FIELDS	SEARCHED			
Minimum d IPC 7	ocumentalion searched (classification system followed by classifica G01S G08G	tion symbols)		
	ulion searched other than minimum documentation to the extent that			
Electronic o	dala base consulled during the international search (name of data baternal	ase and, where pracilcal,	search terms used	
	. ·			
	ENTS CONSIDERED TO BE RELEVANT	· · · · · · · · · · · · · · · · · · ·	 ,	
Category *	Citation of document, with indication, where appropriate, of the re	levant passages		Relevant to daim No.
X	US 5 485 161 A (VAUGHN DAVID) 16 January 1996 (1996-01-16)			1-6,8
Y	the whole document			7
Υ	US 6 201 493 B1 (SILVERMAN DAVID 13 March 2001 (2001-03-13) column 2, line 54 -column 3, line		7	
Y	US 5 977 884 A (ROSS MONTE) 2 November 1999 (1999-11-02) column 2, line 58 -column 4, line		7	
Furth	ner documents are listed in the continuation of box C.	χ Patent family m	nembers are listed in	n annex.
"A" docume consid "E" earlier of filing d "L" docume which i citation "O" docume other n "P" docume	nt which may throw doubts on priority ctalin(s) or is câed to establish the publication date of another no rother special reason (as specified) ant referring to an oral disclosure, use, exhibition or	*T' later document published after the international filling date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention. *X' document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone. *Y' document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combined with one or more other such documents, such combination being obvious to a person skilled in the art. *&' document member of the same patent family		
	actual completion of the International search	Date of mailing of the international search report		
7	July 2003	17/07/2003		
Name and m	nelling address of the ISA European Patent Office, P.B. 5818 Patentiaan 2 NL – 2280 HV Rijswijk	Authorized officer		
	Tel. (+31-70) 340-2640, Tx. 31 651 epo nl. Fax (+31-70) 340-3016	Créchet, P		

INTERNATIONAL SEARCH REPORT

PCT/NL 03/00225

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 5485161	Α	16-01-1996	NONE		
US 6201493	B1	13-03-2001	NONE		·
US 5977884	Α	02-11-1999	NONE		